

# Single-Boom Hydraulic Jumbo



## Vein Runner MTI-1XSB

The MTI XSB Series single-boom hydraulic rig designed for drilling vertical, horizontal and angled holes in underground production headings. It features one hydraulic percussion drifter and can drive headings 12 ft. by 12 ft. (3.66 m by 3.66 m). The CDJ-114N is a one-boom drilling rig designed to drill vertical, horizontal and angled holes for underground production headings. It supports one hydraulic percussion drifter and can drive headings 11 ft. by 12 ft. (3.35 m by 3.66 m).

### Standard Features

- Isuzu C240 diesel engine, 45 hp (34 kw), water cooled, catalytic exhaust purifier, dry element air cleaner
- Hydraulically driven Hamworthy axles, 2 speed drive motors, no-spin differentials, enclosed wet disc spring-apply park brakes
- 50 hp electric power pack driving pumps for percussion/rotation and a pressure compensated piston pump for feed/boom movements
- 12v negative ground engine electrics
- XSB boom for 14 square metres of coverage
- HC-40i Montabert drifter
- ACH-10EL Montabert aluminium feed (10 ft. (3.05 m) rod)
- 10 micron pressure and return filters
- Extendable front jacks
- Safety shut-downs for:
  - engine temperature
  - engine oil pressure
  - hydraulic oil temperature
  - hydraulic oil level
- Two 500 watt drill lights





MINING TECHNOLOGIES  
INTERNATIONAL INC.

*Innovative technologies. Unparalleled support.*


# MTI-1XSB Technical Specifications

Weight:	14,000 lb. (6,364 kg)
Articulation Angle:	40 degrees
Gradeability:	25% (15°)
Turning Radius:	Inside: 6 ft. 7 in. (2.01 m) Outside: 11 ft. 11 in. (3.63 m)
Tire Size:	7.50 x 15
Tramming Speed:	4.5 mph (7.2 km/hr.)
Width:	42 in. (1.06 m)

- Options
- Long hole option
  - Deutz F3L 912W engine, 38hp (28 kw)
  - 46 in. (1.16 m) overall width with 32 x 12 in. solid tires
  - Boom parallelism
  - Aluminium feed for rods up to 13 ft. (3.96 m)
  - Fixed length and telescopic feeds
  - Electric remote drill console
  - Cable reel for 270 ft. (82 m) of cable
  - Fire suppression system
  - Automatic actuation for fire suppression system
  - Operator's canopy
  - Air compressor
  - Water booster pump
  - Rear leveling jacks
  - Large boom 20 m<sup>2</sup>, carrier width 48 in. with 32 x 12 in. solid tires



BOOM COVERAGE DIAGRAM



BOOM COVERAGE DIAGRAM

## VEIN RUNNER MTI-1XSB

Dimensions	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q
Imperial	8'-7"	89"	79-3/4"	63"	14'-1 1/4"	82 3/4"	30'-11"	13'-9"	9"	12'-3"	12'-7"	12'-4"	13'-7"	16'-7"	14'-1"		
Metric	2.62m	2.26m	2.02m	1.65m	4.29m	2.10m	9.24m	4.19m	230mm	3.7m	3.8m	3.76m	4.14m	5.05m	4.29m		



MINING TECHNOLOGIES  
INTERNATIONAL INC.

**Head Office:**  
P.O. Box 2097, Station A  
Sudbury, Ontario, Canada  
P3A 4R8  
145 Magill Street  
Lively, Ontario, Canada  
P3Y 1K6  
Telephone: 1-705-692-3661  
Fax: 1-705-692-4850

**Canadian Sales Office:**  
P.O. Box 2845, Station A  
Sudbury, Ontario, Canada  
P3A 5J3  
25 Fielding Road  
Lively, Ontario, Canada  
P3Y 1L7  
Telephone: 1-705-682-0623  
Fax: 1-705-682-4508  
Toll free: (Canada & U.S.A.)  
1-800-461-8094


**U.S. Sales Office:**  
4953 Bannock Street  
Denver, Colorado, U.S.A.  
80216  
Telephone: 1-303-892-5800  
Fax: 1-303-892-1408  
Toll free: (Canada & U.S.A.)  
1-800-659-4955

**International Sales Office:**  
4953 Bannock Street  
Denver, Colorado, U.S.A.  
80216  
Telephone: 1-303-892-5800  
Fax: 1-303-293-2830  
Toll free: (Canada & U.S.A.)  
1-800-659-4955

**South Africa:**  
P.O. Box 4081  
Dalpark 1543, S.A.  
25, Soetdoring St. Dalpark  
Brakpan, 1540  
Republic of South Africa  
Telephone: 27-11-915-2770  
Fax: 27-11-915-8330

**Australia & South East Asia:**  
26-42 Cooper Road  
Jandakot 6164, W.A.  
Australia  
Telephone: 61-9-417-8488  
Fax: 61-9-417-8747

All specifications, while accurate at time of publication, are subject to change without notice. Some features shown in photos and illustrations may be optional.



Authorized Representative

Made in Canada