


Two-Boom Hydraulic Jumbo



Ramp Runner MTI-2MB

The MTI MB Series two-boom hydraulic rig designed for drilling vertical, horizontal and angled holes in underground production headings. It features two hydraulic percussion drifters and can drive headings 20 ft. by 26 ft. (6.1 m by 7.9 m).

Standard Features

- Deutz F6L 912W diesel engine, 82 hp (54 kw), air cooled, catalytic exhaust purifier, dry element air cleaner
- Clark 18000 series powershift transmission with torque converter, 3 speeds forward/reverse
- 50 hp (37 kw) electric power pack driving pumps for percussion/rotation and a pressure compensated piston pump for feed/boom movements
- 24v negative ground engine electrics
- HC-40i Montabert drifters
- ACH-14 aluminium feed (14 ft. (4.27 m) rod)
- 10 micron pressure and return filters
- Front leveling jacks
- Safety shut-downs for:
 - engine temperature
 - engine oil pressure
 - hydraulic oil temperature
 - hydraulic oil level
- Cable reel with capacity for 350 ft. (107 m) of cable
- Two 500 watt drill lights



**MINING TECHNOLOGIES
INTERNATIONAL INC.**



Innovative technologies. Unparalleled support.

MTI-2MB Technical Specifications

Weight:	44,800 lb. (20,363 kg)
Articulation Angle:	40 degrees
Gradeability:	25% (15°)
Turning Radius:	Inside 12 ft. 8 in. (3.86 m) Outside 23 ft. 7 in. (7.19 m)
Tire Size:	10.00 x 20
Tramming Speed:	9 mph (15 km/hr.)
Width:	7 ft. (2.1 m)

Options:

- HC-80 drifter (c/w a 60 hp (45 kw) power pack)
- Fire suppression system
- Automatic actuation for fire suppression system
- Operator's canopy
- Air compressor
- Water booster pump
- Rear leveling jacks
- 4-71T1 DDEC Engine



BOOM COVERAGE DIAGRAM

RAMP RUNNER MTI-2MB

Dimensions	A	B	C	D	E	F	G	H	J	K	L	M	N
Imperial	8'-1"	90"	7'	87"	11'-10"	69"	40'-11"	4" ON JACKS	27%	12"	26'-8"	20'-9"	18'-9"
Metric	2.45m	2.3m	2.13m	2.21m	3.6m	1.75m	12.47m	101mm	27%	.3m	8.1m	6.3m	5.7m



**MINING TECHNOLOGIES
INTERNATIONAL INC.**

Head Office:

P.O. Box 2097, Station A
Sudbury, Ontario, Canada
P3A 4R8
145 Magill Street
Lively, Ontario, Canada
P3Y 1K6
Telephone: 1-705-692-3661
Fax: 1-705-692-4850

Canadian Sales Office:

P.O. Box 2845, Station A
Sudbury, Ontario, Canada
P3A 5J3
25 Fielding Road
Lively, Ontario, Canada
P3Y 1L7
Telephone: 1-705-682-0623
Fax: 1-705-682-4508
Toll free: (Canada & U.S.A.)
1-800-461-4094

U.S. Sales Office:

4955 Bannock Street
Denver, Colorado, U.S.A.
80216
Telephone: 1-303-892-5800
Fax: 1-303-892-1408
Toll free: (Canada & U.S.A.)
1-800-659-4955

International Sales Office:

4955 Bannock Street
Denver, Colorado, U.S.A.
80216
Telephone: 1-303-892-5800
Fax: 1-303-293-2830
Toll free: (Canada & U.S.A.)
1-800-659-4955


South Africa:

P.O. Box 4081
Dalpark 1543, S.A.
25, Soetdoring Str. Dalpark
Brakpan, 1540
Republic of South Africa
Telephone: 27-11-915-2770
Fax: 27-11-915-8330

Australia & South East Asia:

26-42 Cooper Road
Jandakot 6164, W.A.
Australia
Telephone: 61-9-417-8488
Fax: 61-9-417-8747

All specifications, while accurate at time of publication, are subject to change without notice. Some features shown in photos and illustrations may be optional.



Authorized Representative

Made in Canada