Dump Truck MK-A 20.1Articulated Type, All-Wheel Drive





- Soot particle filter

- Lock-up converter

- Exhaust throttle brake

Transport Capaci	ty Payload		20,000	kg	
	Volume (strucked)		8.4	m^3	
	(SAE, heaped)		10.0	m ³	
Dead Weight			15,000	kg	
Maximum Speed (laden, level)			27	km/h	
Diesel Engine					
Make			Deutz Di	esel	
Type				F 8 L 413 FW, air-cooled, two-stage combustion	
Power Rating (acc. to DIN/ISO)			136 kW		
Driveline	Converter		Clark, C-270		
	Transmission		Clark, R-28000 series		
	Axles	front	Kessler,	D81, planetary type	
		rear	Kessler,	D81, planetary type	
	Tyre size	front / rear	16.00-2	25 / 16.00-25	
	Rim size	front / rear	11.25-2	5/2 / 11.25-25/2	
Brake System	Service brai	ke	Liquid cod	oled multi-disc brakes, full hydraulically operated	
	Parking / en	nergency brake	Multi disc	brake, integrated in transmission	
Steering System	ng System		Hydraulical swivel hinge steering		
Steering angle		± 42°			
Electric System			24 Volts		
Miscellaneous					
Fuel tank capacity			280 l		
Driver's compartment			side-seated (bi-directional operation)		
Optional Equipment and Accessories (e.g.)					
- Exhaustwater scrubber			 Driver's canopy (required for CE-confirmation) 		
- Catalytic exhaust purifier			- Fully enclosed driver's stand		
0 1 1 1 1 1 1			UDD C C C C C C C C C C C C C C C C C C		

- HRD fire extinguishing system

- High altitude kit for engine

