



**High power compact top-hammer long hole drill,  
four wheel drive articulated hydraulic jumbo,  
for fully mechanized production from medium size drifts.  
Compatible to 10 rods carousel.**

**Rock drill**                      *Standard*                      *Alternative*

Model..... Hydrastar 300 L .... Hydrastar 350 L  
Standard male shank.... R 38 - T 38 ..... R 38 - T 38  
Weight ..... 145 kg ..... 155 kg  
Impact frequency ..... 40-55 Hz ..... 40-60 Hz  
Percussion pressure... 160-180 bar ..... 160-180 bar  
Impact power..... 12-16 kW ..... 14-18 kW

**Drill feed**

Model.....LHF 2000  
Steel length ..... 4 to 6 ft  
Drill steel ..... ø 39

**Extension Rod Handler**

Model..... E.R.H.C. 10  
Capacity .....9+1 extension MF rods

**Hydraulic control panel**

Model..... I.C.B.L.  
Providing ..... auto smooth collaring  
precise anti-jamming  
only one control lever for thrust/percussion (full & half)

**Boom**

Model ..... B 26 LC  
Type ..... Parallel holding, multi-directional  
Weight (with hoses) ..... 1900 kg  
Feed roll-over..... 360°  
Boom extension ..... 1200 mm  
Feed extension ..... 1200 mm

**Power Pack**

*Standard*                      *Alternative*  
(for Hydrastar 350 L)

Model ..... P.P. 37 kW/3.2 Q ..... P.P. 45 kW/3.6 Q  
Electrical motor .... 37 kW (50 hp) ..... 45 kW (60 hp)  
Hydraulic pump .....fixed displacement, radial piston

**Tramming possibilities**

Tramming speed ..... up to 6.5 km/h  
Maximum operating grade ..... up to 35%  
Weight, approximate ..... 9600 kg

