



Highly compact rock bolter, four wheel drive hydraulic jumbo, for installation of bolts from 5 to 8 ft in drift of height up to 4.8 m.

Rock drill

ModelHydrastar 200 B
 Standard female shank R 25 - R 32
 Weight 115 kg
 Impact frequency..... 40-65 Hz
 Percussion pressure 140-200 bar
 Impact power..... 6-10 kW

Wrench

Model RHR 40 series
 Weight 45 kg
 Oil pressure..... 160 bar
 Maxi. torque 25 mdaN

Turret

Model TU-C
 Steel length 5 to 8 ft
 Drill steel H 22 till H 28
 Bolt Magazine capacity 10, 12 or 15 bolts
 (depending of bolt used)

Boom

Model..... B 14 B
 Type..... Universal
 Weight (with hoses) 1000 kg
 Feed roll-over 360°
 Boom extension..... 800 mm

Hydraulic control panel

Model..... I.B.C.M.B.
 Providing auto smooth collaring
 precise anti-jamming
 only one control lever for thrust/percussion (full & half)
 greatly reduced number of hoses

Power Pack

Model..... P.P. 37 kW/3.2 Q
 Electrical motor 37 kW (50 hp)
 Hydraulic pump fixed displacement, radial piston

Tramming possibilities

Tramming speed..... up to 6.5 km/h
 Maximum operating grade..... up to 35%
 Weight, approximate..... 9300 kg

